

**In The Claims:**

Add claims 35, 36 and 37 as set forth in the following pages. The entire set of claims 1 through 37 are presented herewith in accordance with the format suggested by the Patent Office in the Flyer dated 02/13/03.

Listing Of Claims:

Claims 1-34 are original claims. Claims 1-8 and 10-29 are elected claims.

Shs  
1. (Original) A catheter assembly comprising:  
at least one tube,  
a companion member, and  
an engagement member connecting said tube and  
said companion member to one another along a zone of said  
tube,

Oh  
said tube and said companion member extending  
proximal of said zone by an amount sufficient to extend out  
of the body of a patient in whom the catheter is embedded,

removal of said engagement member causing said  
tube and said companion member to disconnect and permit  
separate non-surgical withdrawal of said tube and said  
companion member from a patient.

2. (Original) The catheter assembly of claim 1  
further comprising:

a flexible separating prong extending outward  
from the surface of one of said tube and companion member  
to abut the surface of the other at a location proximal of

said zone to force said tube and companion member to diverge away from said zone.

3. (Original) The catheter assembly of claim 1 wherein:

said engagement member is a wire extending proximally to a position outside the patient when the catheter is implanted in a patient,

said wire having a proximal end, said wire being removable by pulling on said proximal end.

4. (Original) The catheter assembly of claim 2 wherein:

said engagement member is a wire extending proximally to a position outside the patient when the catheter is implanted in a patient,

said wire having a proximal end, said wire being removable by pulling on said proximal end.

5. (Original) The catheter assembly of claim 1 wherein:

said engagement member is a set of two wires extending proximally to a position outside the patient when the catheter is implanted in a patient,

said wires each having a proximal end, said wires being removable by pulling on said proximal end.

6. (Original) The catheter assembly of claim 2 further comprising:

a recess on the surface of said tube or companion member against which said prong abuts, said recess engaging the abutting end of said prong to hold said prong in place.

7. (Original) A multiple tube catheter assembly having first and second tubes connected to one another at a predetermined zone, the improvement comprising:

a wire extending longitudinally within said tubes and passing through surfaces of said tubes at said zone to hold said tubes together at said zone,

said tubes being disconnected by withdrawal of said wire.

8. (Original) The catheter of claim 7 wherein said wire is removable by pulling on a proximal end of said wire.

9. (Original) The catheter of claim 7 wherein said wire is a surgical suture.

10. (Original) The catheter of claim 7 wherein said predetermined zone is located on the catheter to be within a patient when the catheter is implanted in a patient.

Oh. 11. (Original) The catheter of claim 7 wherein said wire extends proximally within the sidewall of one of said tubes to a predetermined position within said sidewall outside of the patient when the catheter is implanted in a patient.

12. (Original) The catheter of claim 7 further comprising:

a flexible separating prong extending outwardly from the surface of one of said tubes to abut a surface of the other one of said tubes at a location close to and proximal of said zone, to force said tubes to diverge away from said predetermined zone.

13. (Original) The catheter of claim 11 further comprising:

a flexible separating prong extending outwardly from the surface of one of said tubes to abut a surface of the other one of said tubes at a location close to and proximal of said zone, to force said tubes to diverge away from said predetermined zone.

Q 14. (Original) The catheter of claim 12 wherein: said predetermined zone and said prong are both located on the catheter to be within a patient when the catheter is implanted in a patient.

15. (Original) The catheter of claim 7 further comprising:

a second wire extending longitudinally within said tubes and passing through the connected surfaces of said tubes to hold said tubes together at said zone,

withdrawal of said second wire required to disconnect said tubes.

16. (Original) The catheter of claim 11 further comprising:

a second wire extending longitudinally within said tubes and passing through the connected surfaces of said tubes to hold said tubes together at said zone,

withdrawal of said second wire required to disconnect said tubes.

17. (Original) The catheter of claim 12 further comprising:

a second wire extending longitudinally within said tubes and passing through the connected surfaces of said tubes to hold said tubes together at said zone,

withdrawal of said second wire required to disconnect said tubes.

18. (Original) The catheter of claim 14 further comprising:

a second wire extending longitudinally within said tubes and passing through the connected surfaces of said tubes to hold said tubes together at said zone,

withdrawal of said second wire required to disconnect said tubes.

19. (Original) The catheter of claim 12 further comprising: a recess on the sidewall of said other one of said tubes to receive the end of said separating prong.

20. (Original) The catheter of claim 14 further comprising: a recess on the sidewall of said other one of said tubes to receive the end of said separating prong.

21. (Original) The catheter of claim 18 further comprising: a recess on the sidewall of said other one of said tubes to receive the end of said separating prong.

22. (Original) The catheter of claim 7 wherein: said connected surfaces of said tubes at said zone are flat.

23. (Original) The catheter of claim 12 wherein: said connected surfaces of said tubes at said zone are flat.

24. (Original) The catheter of claim 14 wherein: said connected surfaces of said tubes at said zone are flat.



25. (Original) The catheter of claim 15 wherein:  
said connected surfaces of said tubes at said zone are  
flat.

26. (Original) The catheter of claim 16 wherein: said  
connected surfaces of said tubes at said zone are flat.

27. (Original) The catheter of claim 12 further  
comprising: a reinforcing wire within said prong 27.

28. (Original) A multiple tube catheter assembly  
having first and second tubes connected to one another at a  
predetermined zone comprising:

first and second wires extending longitudinally  
within the sidewalls of said tubes at said zone and passing  
through the connected surfaces of said tubes to hold said  
tubes together at said zone, and wherein said connected  
surfaces of said tubes at said zone are flat, abutting  
surfaces,

said wires extending proximally within the  
sidewall of one of said tubes to a predetermined position  
within said sidewall, said predetermined position being

outside of the patient when the catheter is implanted in a patient,

a flexible separating prong extending outwardly from the surface of one of said tubes to abut a surface of the other one of said tubes at a location close to and proximal of said zone, to force said tubes to diverge away from said predetermined zone, and

a recess in the sidewall of said other one of said tubes to receive the end of said separating prong,

said predetermined zone and said prong being located on the catheter to be within a patient when the catheter is implanted in a patient.

29. (Original) The catheter of claim 28 further comprising: a reinforcing wire within said prong.

30. (Original) The method of retaining and removing a catheter tube in a patient comprising the steps of:

implanting a catheter having a zone in which the catheter tube and a companion member are stitched together with a longitudinal wire wherein the zone is positioned in the patient and the wire extends to a point outside the patient, said zone retaining the catheter in the patient, and

removing the catheter by accessing a proximal portion of said wire, withdrawing said wire and individually removing the catheter tube and the companion member.

31. (Original) The method of retaining and removing a multiple tube catheter in a patient comprising the steps of:

Q1 implanting a catheter having a zone in which at least two tubes are stitched together with a longitudinal wire wherein the zone is positioned in the patient and the wire extends to a point outside the patient, said zone retaining the catheter in the patient, and

removing the catheter by accessing a proximal portion of said wire, withdrawing said wire and individually removing each of said tubes.

32. (Original) The method of claim 31 further comprising the steps of:

during said step of implanting the catheter, providing a separating flexible prong proximal of said zone extending from a first one of said tubes into a recess on the second one of said tubes to hold said tubes apart to prevent distal movement of the catheter, and

during said step of removing the catheter,  
removing said prong from said recess.

33. (Original) The method of implanting and removing a multiple tube catheter implanted in a patient comprising the steps of:

providing a multiple tube catheter assembly, having first and second tubes and a wire extending longitudinally within the sidewalls of said tubes along a predetermined zone and passing through contacting surfaces of said tubes at said zone to hold said tubes together at said zone, said wire extending proximally within the sidewall of said first one of said tubes to a predetermined proximal position,

implanting said assembly in a patient with said zone within the patient and the proximal ends of said wire extending outside of the patient,

accessing the proximal end of said wire,

removing said wire from said catheter to disconnect said tubes at said zone, and

then individually removing each of said multiple tubes from the patient.

34. (Original) The method of claim 33 wherein said step of removing comprises pulling on said wire.

35. (New) The catheter of claim 7 wherein: said connected surfaces of said tubes at said zone includes a dove tail coupling between said surfaces, and wherein said wire extends through the teeth of both sections of said dove tail coupling.

36. (New) The catheter of claim 7 wherein: said connected surfaces of said tubes at said zone include a longitudinal lap joint and wherein said wire extends through the two portions of said lap joint.

37. (New) The catheter of claim 7 wherein:  
a first one of said tubes contains a longitudinal wire having loops at said zones, and  
a second one of said tubes contains said longitudinally extending wire, said wire engaging said loops when said tubes are assembled, the withdrawal of said wire causing said tubes to become disconnected.